

DIGITAL ENCODING ALTIMETER

AD32 DEA80

THOMMEN
AIRCRAFT EQUIPMENT



GENERAL

THOMMEN AD32 digital encoding altimeter (DEA) with extended altitude range suits to every aircraft category including those reaching altitudes above the usual air traffic.

Technically based on the rugged AD32 air data unit design, this DO-178B Level A certified altimeter system exceeds any TSO C10b accuracy requirements throughout the entire altitude range up to 80'400 ft / 24.500 m.

Available in two case designs and with different lighting options incl. optional MIL-STD3009 NVIS green A/B compliance, it easily replaces obsolete mechanical altimeters.

The integrated high-end VCT sensor makes AD32 DEA free from needs for scheduled maintenance or re-calibration.

Together with a fast reacting stepper-motor driven pointer, this sensor type enables virtually "real-time" indication of the altitude also during high-speed vertical maneuvers.

Optionally the system features an integrated altitude alerter (up to FL650) with configurable parameters, altitude preselect,

alerter light and discrete output to a warning tone generator.

The extended barometric setting range from 700...1066 mbar allows QFE operation on high-elevation airfields.

Compliant to TSO C88a, the analogue Gillham gray code (ICAO) is provided to enable direct replacement of older encoders or encoding altimeters.

In parallel, labels 203 (pressure altitude) and 204 (baro corrected altitude) are supplied via two ARINC429 TX channels.

By pressing the optional scale button, the measurement units can be switched between meter and feet and the barometric setting between mbar/hPa and InHg.

Continuous Built-in-Test (BIT) software secures safe operation; the BIT-failure memory can be read out via the RS232 maintenance interface without removing the unit from the aircraft.

PARAMETERS

Pressure Altitude	- 1,000	to	+80,400	feet
Baro Corrected Altitude	1,000	to	+80,400	feet
Altitude Rate physically	0	to	50,000	feet/min.
Altitude Rate submitted per ARINC 429 label 212	0	to	32,768	feet/min.
Baro Setting Range	20.67	to	31.48	inHg
	700	to	1,066	Mbar/hPa

DIGITAL ENCODING ALTIMETER

AD32 DEA80



CHARACTERISTICS

FEATURES:	Vibration Cylinder Technology (VCT) static pressure sensor English/metric scale setting Baro Push-to-Reset function Push-to-Test and continuous Built-In-Test BIT Failure memory Display with LCD / stepper motor driven pointer RS232 Maintenance Interface 28V or 5 V lighting power White, white-red or white-green-NVIS green lighting	SIGNAL OUTPUTS:	ARINC 429 data bus 2 transmit channels
SIGNAL INPUTS:	Primary power 28 VDC Emergency power 28 VDC Lighting power 28 VDC (Optional 5 VDC) ARINC 429 serial data bus 2 receive channels	OPERATING SPECIFICATIONS:	Altitude Scale Error - 1,000 to 20,000 feet ± 10 feet 20,000 to 29,000 feet ± 20 feet 29,000 to 41,000 feet ± 30 feet 41,000 to 53,000 feet ± 50 feet 65,000 to 80,000 feet ± 150 feet FAA TSO-C10b/TSO-C88a (applies up to 53'000 ft) RTCA/DO-178B Level A RTCA/DO-160D - Operating Temperature -30° ... 70°C - Storage Temperature -55° ... 85°C Reliability: MTBF 21,000 hours
SIGNAL OUTPUTS:	Encoded Altitude ICAO Per TSO C-88a Warning Flag Valid GND/28 VDC Optional Baro Potentiometer Output		

MECHANICAL DRAWING

